

外径OD		壁厚 Wall Thickness		端部加工形式 End Finish	钢 级Grade	类 型Type
in	mm	in	mm			
10 <sup>3/4</sup>	273.1	0.279	7.09	STC	J55	ERW
		0.350	8.89	STC、BTC	J55	ERW
		0.350	8.89	STC、BTC	J55、K55	无缝钢管Seamless
		0.400	10.16	STC、BTC	J55	ERW
		0.400	10.16	STC、BTC	J55、K55	无缝钢管Seamless
		0.450	11.43	STC、BTC	J55、K55、N80、L80	无缝钢管Seamless
13 <sup>3/8</sup>	339.7	0.330	8.38	STC	J55	ERW
		0.380	9.65	STC、BTC	J55	ERW
		0.380	9.65	STC、BTC	J55、K55	无缝钢管Seamless
		0.430	10.92	STC、BTC	J55	ERW
		0.430	10.92	STC、BTC	J55、K55	无缝钢管Seamless
		0.480	12.19	STC、BTC	J55、K55、N80	无缝钢管Seamless
		0.514	13.06	STC、BTC	N80	无缝钢管Seamless
16	406.4	0.375	9.53	STC	H40	无缝管Seamless ERW
		0.438	11.13	STC BTC	J55 K55	无缝管Seamless ERW
		0.495	12.57	STC BTC	J55 K55	无缝管Seamless ERW
18 <sup>5/8</sup>	473.1	0.435	11.05	STC BTC	H40 J55 K55	无缝管Seamless ERW
20	508	0.438	11.13	STC LTC BTC	H40 J55 K55	无缝管Seamless ERW
		0.50	12.70	STC LTC BTC	J55 K55	无缝管Seamless ERW
		0.635	16.13	STC LTC BTC	J55 K55	无缝管Seamless ERW

#### 钻杆规格参数

#### Specifications for Drill Pipe

外 径 OD In mm	名义重量 Nominal Weight lb/ft	钢 级 Grade	壁 厚Wall Thickness		加厚型式 Upset
			In	mm	
2 <sup>3/8</sup> 60.3	6.65	E X G S	0.280	7.11	EU
2 <sup>7/8</sup> 73.0	10.40	E X G S	0.362	9.19	EU IU
3 <sup>1/2</sup> 88.9	13.30	E X G S	0.368	9.35	EU IU
	15.50	E X G S	0.449	11.40	EU IEU
4 101.6	14.00	E X G S	0.330	8.38	EU IU
4 <sup>1/2</sup> 114.3	16.60	E X G S	0.337	8.56	EU IEU
	20.00	E X G S	0.430	10.92	
5 127.0	16.25	E X G S	0.296	7.52	IU
	19.50	E X G S	0.362	9.19	EU IEU
	25.60	E X G S	0.500	12.7	
5 <sup>1/2</sup> 139.7	21.90	E X G S	0.361	9.17	IEU
	24.70	E X G S	0.415	10.54	