

特种车辆

SPECIAL VEHICLES

吸污车 VACUUM SUCTION SEWAGE TRUCK

SHL 型吸污车，该车是在二类汽车底盘基础上加装专用装置改装而成的特种车辆。主要由真空泵、油气分离器、气水分离器、防溢阀等专用设备组成，主要用于收集、中转、清理油田洗井废液等液态污物，避免二次污染。具有容积大，重心低，行驶平稳，外形美观大方，多功能，高效率，经济效益高等优点。

SHL vacuum suction sewage truck is a special purpose vehicle completed with special units on the chassis of category 2, mainly composed of vacuum pump, oil-gas separator, moisture separator, relief valve and other special units, aiming for collecting, transferring, disposing liquid wastes generated by oil field well washing, so as to avoid environment secondary pollution. The truck features large volume, stable traveling, low center of gravity, smart appearance, multi-Function, high efficiency and high economic return, etc.



产品特点

- ◆ 运移性好，地区适用性强，设备利用率更高；
- ◆ 抽吸效率高、自吸、自排及直灌；
- ◆ 工作速度快，运输方便，劳动强度低；
- ◆ 结构更紧密，可以耐更高压力提供更大的吸力，吸程远；
- ◆ 真空度高、吨位大、效率高、用途更广泛；
- ◆ 操作简便、提高效率、降低成本、安全性能好；
- ◆ 低噪声，低能耗，使用方便，寿命长；
- ◆ 投资少，维护操作方便，性能优良，节能环保。

Features

- ◆ Fast transportation and adaptable to complex road conditions lead the truck used frequently;
- ◆ High efficiency in suction, available for self priming, self-drainage and direct irrigation;
- ◆ High working speed and easy transportation deliver reduced labor intensity ;
- ◆ Compact structure withstanding higher pressure offers greater pull of suction and super suction head;
- ◆ Large capacity with high vacuum realizing high efficiency and wide application;
- ◆ Simple operation, improved efficiency, reduced cost and stable safety ;
- ◆ Low noise and energy consumption, long lifetime;
- ◆ Low investment, easy to operate and maintain, excellent performance, energy-saving and low emission .

主要参数 Specifications

产品名称 product	吸污车 Vacuum Suction Sewage Truck
环境温度 Ambient Temperature	- 20 ~ 60°C
介质温度 Medium Temperature	10 ~ 45°C
最大真空度 Vacuum Degree	≥ 0.4kPa
抽气真空泵转速 Rotational Speed, Suction Vacuum Pump	500r/min
最大流量 Max. Flow	4000L/min
罐体容积 Tank Capacity	14m ³
最大爬坡能力 Max. Gradeability	30%
整车总质量 Total Weight, kg	25000kg
外型尺寸 Overall Dimension, mm	10120 × 2500 × 3190mm